



RANGE  
**PLC**

## ROAD PLANERS

SELF-LEVELLING WITH CONVEYOR BELT

PLC 18

PLC 24

PLC 30

PLC 40

- Clean trench
- Constant planing depth
- Perfect surfaces with side-by-side passes
- Max. safety
- Stability and no vibrations
- Excellent visibility for the operator

# ROAD PLANERS

SELF-LEVELLING WITH CONVEYOR BELT

PLC 18  
PLC 24  
PLC 30  
PLC 40



Simex PLC self-levelling planers clean the milled trench and deposit the dug material to the right or left. Thanks to the self-leveling system, planing depth is constant in any condition.

They are indispensable for optimizing collection of milled material for reuse on site or for transporting away.

Can be installed with spray system for dust control.

**SIMEX** **PERFORMER**  
• patent •



## ADVANTAGES

- Clean trench
- Constant planing depth
- Perfect surfaces with side-by-side passes
- Max. safety
- Stability and no vibrations
- Excellent visibility for the operator

TECHNICAL DATA		PLC 18	PLC 24	PLC 30	PLC 40
Standard drum width	mm inch	450 18	600 24	750 30	1000 40
Max. depth	mm inch	150 6	170 7	170 7	130 5
Depth adjustment		Independent RH-LH, mechanical – hydraulic optional			
Side shift		Hydraulic			
Transverse tilt		Automatic			
Tilt		16°			
Operating weight <sup>(1)</sup>	kg lbs	945 2080	1100 2400	1200 2650	1360 3000
Required oil flow	l/min gpm	85 - 120 22 - 32	100 - 150 27 - 40	110 - 170 29 - 45	110 - 190 29 - 50
Max. oil pressure	BAR psi	300 4350	300 4350	300 4350	300 4350

(1) User is responsible for ensuring that the characteristics of the prime mover suit the weight and specifications of the attachment.

Simex does not accept responsibility or liability for the information provided. Technical modifications may vary without prior notice.

